


PINNACLE SERIES

Cross Cable High Peak Frame Tent



SPECIFICATIONS	Competitor Tents	CELINA Pinnacle Tents
MATERIAL	 <p>16oz / 560gsm black out PVC fabric Waterproof, Flame Retardant No mold/mildew protection • No ongoing testing</p>	 <p>16oz / 580gsm black out PVC fabric Waterproof, Flame Retardant (NFPA-701 / CAN-ULC-S109) Anti-UV (1000 hours), Anti-Cold Crack (-22F° / -30C°) Anti-Wicking, Anti-Mildew • Full PVC test every year</p>
TUBING	 <p>6005-T5 Aluminum 0.123" (3.13mm) wall thickness Hardness: 13HW</p>	 <p>6061-T6 Aluminum 0.128" (3.25mm) wall thickness Hardness: 16HW</p>
FITTINGS	 <p>Thinner, lightweight aluminum Corner Fitting • 0.18" (4.46mm) wall thickness Spreader insert • Aluminum + Steel, Heavier, Rust</p>	 <p>Thicker, more durable aluminum Corner fitting 0.26" (6.65mm) wall thickness, Reinforced hook • Spreader insert Heavy duty aluminum</p>
BASE PLATE ANCHOR	 <p>20" Straight anchor</p>	 <p>24" Anchor with hook</p>
VERTICAL TENSION	 <p>Rope Weathers quickly</p>	 <p>1" Ratchet strap assembly</p>
WIND KIT	 <p>Optional accessories 1.5" rope tension, 24" stakes Tent at risk of collapse in poor weather</p>	 <p>Included with tent 2" ratchet strap assembly, 36" stakes Wind kit steadies tent against wind & rain</p>
CORNERS	 <p>Steel open S shape hook Easy to slip off No corner flaps</p>	 <p>Galvanized steel, closed carabiner Stronger, more stability Corner flap secures each corner</p>
TENT TOP EDGE	 <p>Rope edge Weathers quickly, loses tension</p>	 <p>1" webbing reinforced overlapped edge Increased durability and longevity</p>